MEMPHIS

IAP, AD

H-6J, L-18G

MEMPHIS INTL (MEM)(KMEM) P (ANG) 3 S UTC-6(-5DT) N35°02.54′ W89°58.60′

341 B LRA ARFF Index—See Remarks NOTAM FILE MEM RWY18C-36C: H11120X150 (CONC-GRVD) S-125, D-210, 2S-175,

2D-458, 2D/2D2-873 PCN 82 R/C/W/T HIRL CL

RWY 18C: MALSR. TDZL. RVR-TMR Pole. 0.7% up.

RWY 36C: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR Tree. Rgt tfc. 0.6% down.

RWY18R-36L: H9320X150 (CONC-GRVD) S-125, D-210, 2S-175, 2D-458, 2D/2D2-873 PCN 82 R/C/W/T HIRL CL

RWY 18R: MALSR, TDZL, RVR-TMR Rgt tfc.

RWY 36L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TMR Road, 0.5% down

RWY18L-36R: H9000X150 (CONC-GRVD) S-125, D-210, 2S-175, 2D-458, 2D/2D2-873 PCN 82 R/C/W/T HIRL CL

RWY 18L: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TMR 0.8% up.

RWY 36R: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 69'. RVR-TMR Trees. 0.5% down.

RWY 09–27: H8946X150 (CONC–GRVD) S–125, D–178, 2S–175, 2D–602, 2D/2D2–870 PCN 92 R/B/W/T HIRL CL

RWY 09: MALSR, RVR-TR Pole, 0.3% up.

RWY 27: MALSR. PAPI(P4L)—GA 3.0° TCH 69′. RVR–TR Pole. 0.6% down.

HOLD_SHORT POINT

LAND AND HOLD-SHORT OPERATIONS

I DC RWY

LDU KIII	HOLD CHOKE I CHE	A.	DE EDU DIOI
RWY 27	TWY N	8450	
RUNWAY DECLARED DISTANCE INFORMATION			
RWY 09: TORA-8946	5 TODA-8946 A	ASDA-8946	LDA-8946
RWY 18C:TORA-111:	20TODA-11120 A	ASDA-11120	LDA-11120
RWY 18L:TORA-9000	O TODA-9000 A	ASDA-9000	LDA-9000
RWY 18R:TORA-932	0 TODA-9320 A	ASDA-9320	LDA-9320
RWY 27: TORA-8946	5 TODA-8946 A	ASDA-8946	LDA-8946
RWY 36C:TORA-111:	20TODA-11120 A	ASDA-10715	LDA-10715
RWY 36L:TORA-9320	O TODA-9320 A	ASDA-9320	LDA-9320
RWY 36R:TORA-900	0 TODA-9000 A	ASDA-9000	LDA-9000

Residential Area of a state of the state of

ARRESTING GEAR/SYSTEM RWY 18R: EMAS

SERVICE: S4 FUEL 100LL, JET A, A+, A++ 0X 1, 2 LGT Rwy 36R ALSF-2 also opr as SSALR. Rwy 36R ALSF2 unmonitored. MILITARY—A-GEAR Rwy 18R EMAS 316 x 178. JASU 1(MD-3) 5(MD-3M) 1(MA-1A) 2(MC-2A) 2(A-7) FUEL A, A+ (C901-345-2992) A++ (Mil) (ANG PPR DSN 726-7131, C901-291-7131. Copter refuel is 2 nozzle.) (NC-100LL) FLUID SP PRESAIR LOX 0IL 0-156(Mil)

AVRI INC DIST

AIRPORT REMARKS: Attended continuously. Class I, ARFF Index C. Index D ARFF eqpt avbl 24 hrs per day, 7 days per wk. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. If possible all acft conduct gnd ops with transponders on. NS ABTMT procedures in effect. Successive and/or simultaneous departures apvd on Rwy 36L-18R and Rwy 36C-18C or Rwy 36L-18R and Rwy 36R-18L with course divergence no later than 2.27 NM from rwy end. Extv const on arpt. Large flocks of birds invof arpt. Read back all hold short instr req. Single belly twin tandem Idg gear max wt 621,000 lbs. PPR for taxi clnc on Twy N north of Twy V, Twy S north of Twy V and Twy C north of Twy V ctc Federal Express Ramp Twr on freq 131.5. PPR for taxi clnc from north and south cargo ramp parking on freq 121.9. Helicopter ops prohibited to/from terminal bldg. Twy N north of Twy V, Twy C north of Twy V and Twy S north of Twy V designated as non-movement areas. Twy P1 is designated as a non-movement area. Twy P2 in a non-movment area indef. Large and heavy eastbound acft on Twy V for Rwy 27 hold short at minimum thrust area sign. Acft with wingspans greater than 171 '6" rstd fm taxi on Twy N btn Twy M7 and Twy T. Acft with wingspans greater than 118' restricted from taxiing on Twy J north of Twy C3. Twy V btn Spot 7W and AER 27 rstd to acft with wingspans of 171 '6" or less. Twy V btn Twy S and Twy Y rstd to acft with tail hgt less than 65 '10". Twy N btn AER 09 and Taxilane N clsd to acft wingspan more than 171' indef. Twy P1 btn Twy T and terminal ramp clsd indef. Twy P2 btn Twy T and terminal ramp clsd indef. Flight Notification Svc (ADCUS) avbl. NOTE: See Special Notices—Noise Abatement Procedures and Continuous Power Facilities.

CONTINUED ON NEXT PAGE

416 TENNESSEE

CONTINUED FROM PRECEDING PAGE

MILITARY REMARKS: ANG PPR 24 hr prior notice rgr, ltd to official business only. PPR DSN 726-7131/7505,

C901–291–7131/7505. MIL Ramp OPS 1230–0430Z‡ Mon–Fri, CLOSED altn Mon and HOL due altn work SKED. MIL Ramp CLOSED outside of publ HR without OG/CC apvl DSN 726–7557, C901–291–7557. MIL ramp OPS at reduced ARFF, downgraded to yellow. Tran acft maint not avbl. Refuel svc for other than C17 acft rqr qualified crew chief or crew members. Non C17 acft support provided by contract FBO on fld. Security avbl 24 hr, DSN 726–7101 or

Mon-Fri, clsd alternate Mon and hol due to alternate work sked. Afld mgr does not issue or store COMSEC for tran crews. Tmpry storage of classified materials up to TOP SECRET at Comd Post. BASH Phase II Apr-May and Aug-Oct; current Bird Watch cond are not rpt on ATIS. ATIS info reports bird activity H24 in area.

AIRPORT MANAGER: 901-922-8000

WEATHER DATA SOURCES: ASOS 127.75 (901) 842-8483. TDWR.

COMMUNICATIONS: D-ATIS 127.75 UNICOM 122.95

RCO 122.2 (JACKSON RADIO)

® APP CON 119.1 (176°-355°) 125.8 (356°-175°)

TOWER 118.3 (Rwy 09-27) 119.7 (Rwy 18C-36C, Rwy 18L-36R) 128.425 (Rwy 18R-36L)

GND CON 121.0 (Rwy 09-27) 121.65 (Rwy 18R-36L) 121.9 (Rwy 18C-36C, Rwy 18L-36R) CLNC DEL 125.2

® DEP CON 124.15 (356°-175°) 124.65 (176°-355°)

CPDLC (LOGON KUSA)

AIRSPACE: CLASS B See VFR Terminal Area Chart.

VOR TEST FACILITY (VOT) 111 O

RADIO AIDS TO NAVIGATION: NOTAM FILE MEM.

(H) VORTACW 117.5 MEM Chan 122 N35°00.91′ W89°58.99′ 010° 1.7 NM to fld. 363/1E.

ILS 109.5 I-MEM Rwy 09. Class IB. LOC unusable byd 20° right and 25° left of course.

ILS 111.95 I-SDU Rwy 18C. Class IE.

ILS/DME 111.15 I-EXS Chan 48(Y) Rwy 18L. Class ID.

ILS 109.9 I-OOI Rwy 18R. Class IA.

ILS 108.7 I-JIM Rwy 27. Class IA. Glideslope unusable byd 9 NM.

ILS/DME 110.5 I–TSE Chan 42 Rwy 36C. Class IIIE. LOC unusable byd 20° left and 20° right of course. Due to multiple clearance unlocks.

ILS/DME 108.9 I-OHN Chan 26 Rwy 36L. Class IIIE.

ILS/DME 111.35 I-MYO Chan 50(Y) Rwy 36R. Class IIIE.

COMM/NAV/WEATHER REMARKS: VOR Test Facility (VOT) unreliable.

MERSY N35°30.95′ W88°57.42′

NDB (MHW) 394 MKL 023° 5.4 NM to Mc Kellar-Sipes Rgnl. 784/1W.

MEMPHIS

MILLINGTON

CHARLES W BAKER (2M8) 4 SW UTC-6(-5DT) N35°16.71′ W89°55.98′

MEMPHIS L-16H

IAΡ

247 B NOTAM FILE MKL

RWY 18-36: H3499X74 (ASPH) S-25 MIRL RWY 18: REIL. PAPI(P2L)—GA 4.0° TCH 40'. Tree.

RWY 36: REIL. PAPI(P2L)—GA 4.0° TCH 40′. Tower. Rgt tfc.

RWY 18U-36U: H1600X75 (ASPH) S-4

RWY 18U: Tree.

RWY 36U: Trees.

SERVICE: FUEL 100LL, JET A+

AIRPORT REMARKS: Attended Mon–Fri 1300–2100Z‡. Unattended Thanksgiving and Christmas. Attended 8:00 am to 4:30 pm all federal holidays. Fixed–wing tkf/ldg prohibited from/to grass areas. Rwy 18U–36U clsd perm.

AIRPORT MANAGER: 901-358-0028

WEATHER DATA SOURCES: AWOS-A 122.8 (901) 873-0903.

COMMUNICATIONS: CTAF/UNICOM 122.8

® MEMPHIS APP CON 125.8

® MEMPHIS DEP CON 124.15

CLEARANCE DELIVERY PHONE: For CD ctc Memphis Apch at 901-842-8457.

RADIO AIDS TO NAVIGATION: NOTAM FILE MEM.

MEMPHIS (H) VORTACW 117.5 MEM Chan 122 N35°00.91′ W89°58.99′ 008° 16.0 NM to fld. 363/1E.

SE, 26 MAR 2020 to 21 MAY 2020